

## System



CPU	Intel® Atom™ Processor Z510/Z530
Cache Memory	512K 2nd Level Cache Memory
System Chipset	Intel System Control Hub US15W
System Memory	Default 256MB, maximum up to 2GB (SO-DIMM, 1 x 200-pin DDR2 533)
SSD	Support One CompactFlash Card
HDD Drive	Built-in One 2.5" SATA HDD bay

## I/O Connectivity

Serial Port	COM1, COM2, COM5 (w/ pin9 +5V/+12V for all ports)
Parallel Port	1 x Bi-directional Parallel ( D-Sub25 )
USB	"Default 3 x USB 2.0 (Front x1, Backx2) Optional expansion 4 USB2.0 ports, total up to 7 USB2.0 ports"
VGA output	support 15 pin D-Sub VGA output
Audio	"Line-out x1, Mic-in x1, Plug ON Disable SPK"
Cash Drawer	"1 x 12V Cash Drawer RJ11 connector (single / dual)"
Ethernet	1 x RJ45 10/100/1000 Base-T (Giga LAN)
OS support	"Win XP (Pro, Embedded) WEPOS and Linux"

## Advanpos Dedicated Connector (Optional)

LVDS output	1024*768 250nits LCD
COM	Touch panel
USB	WiFi, RFID, MSR+FingerPrint
PS2	MSR, MSR+I-Button

## Mechanical & Environment

Dimensions	235(L) x 163.5(W) x 64(H) mm
Construction	Aluminum Die-Casting Enclosure
Weight	2.5KG
Temperature	0°C ~ 35°C Operating
Power Supply	80W 12Vdc Power Adapter
EMI/Safety	CE, FCC, UL, RoHS