

System Specification

Model number	Cubee Series			
	C-615	C-615V	C-815	C-815V
LCD & Touch Panel				
LCD Panel	15" TFT			
MAX. Resolution	1024 x 768 (Default)			
Brightness	250 cd/m ²			
Touch Screen	5-wire Resistive (Default RS232)		5-wire Resistive (Default USB)	
System Configuration				
CPU	Intel® Atom™ D525 dual core 1.8GHz		Intel® Celeron® B810E dual core 1.6GHz (support i3/i5 CPU)	
Chipset	ICH8M		Intel® HM65 Express Chipset	
System Memory	204Pin DDR3 RAM*2 slots, Up to 4GB		204Pin DDR3 RAM*2 slots, Up to 8GB	
BIOS	Phoenix Award BIOS		AMI SPI BIOS	
Graphic Memory	Shared memory up to 224MB			
HDD	1 x 2.5" SATA HDD or 1 x 1.8"/2.5" SSD			
SATA DOM	Support 1GB to 16GB			
I/O Ports				
Parallel Port	1 x LPT port (optional,cable output)			
Serial Ports	3 x DB-9 COM ports (COM1/3/4) 1 x RJ-45 COM port (COM5) (All with DC 5V/12V output on Pin 9 selectable)		3 x DB-9 COM ports (COM1/2/6) 1 x RJ-45 COM port (COM4) (All with DC 5V/12V output on Pin 9 selectable)	
USB Ports	6 x USB 2.0 ports			
LAN Port	1 x (10/100/1000M bps auto)			
Keyboard Port	1 x PS/2 keyboard			
Audio Port	1 x Line out			
VGA Port	1 x DB-15 VGA port			
Cash Drawer Port	1 x RJ-12 port (COM Port control 12V/24V selectable)		1 x RJ-12 port (GPIO, 12V/24V selectable), support 2 cash drawers by Y-cable	
Speaker Output	2 x 1W speaker			
DC Output	1 x DC 12V output			
Powering System				
Power Supply	DC24V 120W external power supply (placed inside the system base) AC 90V to 264V full range			
Power Button	1 x System on/off button			
Brightness Control	2 buttons for LCD brightness adjustment			
Physical Dimensions				
Wall mount	N/A	VESA 75*75mm compliant	N/A	VESA 75*75mm compliant
System Dimension (L x W x D)	329*348*213mm	267*348*75mm	329*348*213mm	267*348*75mm
System Weight	9Kg	6Kg	9Kg	6Kg
Safety & Environment				
Product Certification	CE / FCC/CCC/CB/BSMI/LVD Certified			
Operation Temperature	0°C to 40°C			
Storage Temperature	-25°C to 70°C			
OS Compatibility	Windows XP Pro / Windows 7 / WEPOS / POSReady 2009 / POSReady 7 / Linux Kernel 2.6 or above			

Adding flexibility and functionality to POS operation



VFD/LCM
Customer Display



10.4"/12.1"
2nd LCD Display



3-in-1 reader



Integrates scanner
(C-615V/C-815V)



Cubee 615/815

15" Simple, Practical, Valuable
Touch POS Terminal





The Ultimate Future-proof POS Terminal Guarantees Lowest Total Cost of Ownership



The right way to evaluate a POS system is not just by the upfront costs but the total cost over time. We are confident that the revolutionary system design of DataVan Cubee providing superior flexibility, upgradeability and serviceability, which deliver great value-added features. Come enjoy the competitive edges today.



■ Sleek yet practical design



Ultra slim bezel



0°~90° LCD tilt angle for operating comfort



Adapter storing inside the stand



Easy cable management



Easy-access I/O ports



■ Snap into place automatically

The patented revolutionary tray design for future upgrade flexibility

Individual tray for system core engine



Snap-out hard drive



intel Celeron inside intel Atom inside
B810E D525
1.6GHz 1.8GHz

■ Fits various retail & hospitality environments



Countertop



Wall mount