

DELTA 3000



Specification

Model number:	Delta-3000
System Configuration	
CPU	Support Intel CPU from Celeron / Pentium Dual Core / Core 2 Duo CPU Series. From E1500 Up to E7400
Chip Set	North Bridge: Intel 945G / GC South Bridge: ICH7R
Main Memory	240-Pin DDR2 SDRAM Socket * 2 up to 4GB. (DDR 2 533 / 667 FSB)
Graphic Memory	System shared Memory up to 224MB
HDD	2 x 2.5" SATA HDD
I/O Connectivity	
Parallel Port	1 x LPT port (SPP/EPP/ ECP). IRQ and address selectable by BIOS setup
Serial Port	3 x DB-9 COM ports. All with DC5V/12V output on Pin 9 selectable
USB Port	4 x USB2.0 port (2 x front, 2 x rear)
Power USB Port	3 x USB2.0 port(12Vx2, 24Vx1)
LAN Port	1 x (10/100/1000M bps auto)
Audio Port	1 x Line in, 1 x Line out, 1 x MIC in
Graphic Port	1 x DB-15 VGA connector 1 x DVI-D port
Powering System	
Power Supply	Adapter: Full Sealed DC 24V/ 200W External Power Adapter with Active PFC. AC 90 to 264 V Full Range.
Physical Dimensions	
Dimension (W x L x D)	Product: 310 x 293 x 90 mm Packing: 450 x 403x 183 mm
Safety & Environment	
Product Certification	CE / FCC Class A / LVD certificated
Operation Temperature	0 °C to 40 °C
Storage Temperature	-25 °C to 70 °C
S/W Compatibility	WIN XP/ WEPOS / POSReady 2009 / WINDOWS 7/ POSReady 7 / WINDOWS 8 / Linux Kernel 2.6 or above.

* Specifications subject to change without prior notice

